RIO 125 LED 7936

astro

Not Applicable

1.25 (Kg)

SKU 1325007



PRODUCT SPECIFICATION

GENERAL

FINISH: Plaster CABLE LENGTH:

MAIN MATERIAL: Plaster GROSS WEIGHT:

DIMENSIONS: H: 210mm W: 125mm D: 55mm CLASS:

DIMENSIONS:H: 210mm W: 125mm D: 55mmCLASS:CE (Class I)INSTALLATION ORIENTATION:Wall MountIP RATING:IP20

INSTALLATION ORIENTATION:Wall MountIP RATING:IP20CUT OUT HOLE:Not ApplicableBATHROOM ZONE:Zone 3RECESS DEPTH:Not ApplicableVOLTAGE:Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:High Power LEDMACADAM ELIPSE:3-Step

MAXIMUM WATTAGE:5.7WUGR:Not ApplicableMAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:Not Applicable

LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable
LUMINOUS FLUX: 266.6 (Im) ROTATION ADJUSTMENT ANGLE: Not Applicable
COLOUR TEMP: 2700 (K) AVERAGE LIFESPAN: To Be Advised

CRI: 80 L70: To Be Advised R9: -18.0

ELECTRICAL

SWITCHED: No SUPPLY FREQUENCY: 50/60 (Hz)


DIMMABLE: No DRIVER/BALLAST VOLTAGE: 100-240 (V)

DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 30000 (Hrs)

DRIVER OUTPUT CURRENT:700 (mA)EFFICACY:46.77 (lm/W)DRIVER OUTPUT VOLTAGE:Not ApplicableDRIVER/BALLAST INCLUDED?Yes (Integral)

ADDITIONAL INFORMATION





THIS PRODUCT CAN BE SPRAY PAINTED

CE

