

# PRODUCT DATASHEET SMART ZB PAR16 50 4.7W 220V TW GU10

SMART+ SPOT GU10 TW | LED retrofit reflector lamps with smart home technology, color temperature adjustable, PAR16



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

#### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

#### **Product features**

- Controllable via compatible smart home system (gateway and app)
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Network protocol: ZigBee 3.0
- Dimmable
- Lifetime: up to 20,000 h
- For full functionality connection to a compatible smart home System (gateway and app) required



## **TECHNICAL DATA**

## Electrical data

Nominal wattage	4.7 W
Construction wattage	4.70 W
Nominal voltage	220240 V
Nominal current	38 mA
Mains frequency	50 Hz
Power factor λ	> 0.5
Claimed equiv. conventional lamp power	50 W

#### Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	350 lm
Luminous flux	350 lm
Luminous efficacy	74 lm/W
Luminous intensity	700
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4



# Light technical data

Beam angle	45 °
Starting time	< 0.5 s

# **Dimensions & Weight**



Product weight	43.00 g	
Diameter	50.00 mm	
Maximum diameter	50 mm	
Length	54.00 mm	
Width	50 mm	
Height	50 mm	
Outer bulb [PICOS]	PAR51	
Lifernan		
Lifespan		
Number of switching sucles	100000	

Number of switching cycles	100000
Lifespan	20000 h

#### Colors & materials

Product color	Transparent
Housing color	Transparent

# Temperatures & operating conditions

Ambient temperature range	-2040 °C

# Additional product data

## Capabilities

Dimmable	Yes	
Compatible smart home technology	Amazon Alexa / Google Assistant / Philips Hue	

#### Certificates & Standards

Energy efficiency class	F
Energy consumption	5.00 kWh/1000h
Standards	CE
Type of protection	IP20

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	GU10
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	<b>⊠</b> 0.5 W
Networked standby power for CLS	<b>⊠</b> 0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	> 0
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	1160676
Model number	AC41290

### **DOWNLOAD DATA**

	Documents and certificates
PDF	Installation guide
PDF	Declarations Of Conformity CE
PDF	Declarations Of Conformity UKCA
	Photometric and lighting design files
	Spectral power distribution

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075729162	Folding box 1	61 mm x 78 mm x 96 mm	124.00 g	0.46 dm³
4058075729179	Shipping box 4	173 mm x 108 mm x 141 mm	585.00 g	2.63 dm <sup>3</sup>
4058075760202	Shipping box 32	359 mm x 229 mm x 303 mm	4928.00 g	24.91 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.