

# PRODUCT DATASHEET SMART WIFI PIN 3,5W 827 230V TW CL G9

SMART+ WIFI PIN G9 TUNABLE WHITE | LED lamps with retrofit pin base G9 with WiFi technology



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

### Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

#### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Lifetime: up to 20,000 h






#### **TECHNICAL DATA**

#### Electrical data

Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220240 V
Nominal current	28 mA
Operating frequency	5060 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	0.40
Claimed equiv. conventional lamp power	30 W
Operating mode	AC Mains

## Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	320 lm
Luminous flux	320 lm
Luminous efficacy	91 lm/W
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



# Light technical data

Beam angle	300 °
Starting time	0.5 s

# Dimensions & Weight



Product weight	10.00 g
Diameter	18.00 mm
Maximum diameter	18 mm
Length	60.00 mm
Width	18.00 mm
Height	18.00 mm
Outer bulb [PICOS]	T18

# Lifespan

Number of switching cycles	100000
Lifespan	20000 h

#### Colors & materials

Housing color	Transparent
Body material	Plastic

# Temperatures & operating conditions

## Additional product data

Base (standard designation)	G9

## Capabilities

Dimmable	Yes
----------	-----

# Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	4.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G9
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0.50
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.42
R9 Colour rendering index	>0
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	> 0.4
LED light source replaces a fluorescent light source	No
EPREL ID	1452501
Model number	AC47300

#### **EQUIPMENT / ACCESSORIES**

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## DOWNLOAD DATA

	Documents and certificates
PDF	Installation guide
PDF	Declarations Of Conformity CE

#### Documents and certificates



Declarations Of Conformity UKCA

#### Photometric and lighting design files



Spectral power distribution

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075826656	Folding box 1	42 mm x 80 mm x 98 mm	48.00 g	0.33 dm <sup>3</sup>
4058075826663	Shipping box 4	173 mm x 108 mm x 98 mm	253.00 g	1.83 dm <sup>3</sup>
4058075826670	Shipping box 32	359 mm x 229 mm x 216 mm	2339.00 g	17.76 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

G9