

LED CORN LAMPS GKS28



15W

19W




24W



S28-15W

S28-19W

S28-24W



Specifications

Power	led Qty	PF	CRI	Voltage	CCT	Lumen	Size mm (x 0.039=inch)	Operation tep (°C/F)	Weight (lbs=2.2*kg)	Certificate	Equal to
15W	45 leds LG5630	≥0.9	≥80	100-277VAC	1900-6500K	1950±200lm	E26 Φ64*146	minus 40~60°C	NW 0.29kg	LM79 TM21 UL/cUL/RoHS UL1598C	50w MHL/HPS
							G24-Q Φ64*134				
							G24-D Φ64*141	minus 40~140°F	GW 0.33kg		
19W	54 leds LG5630	≥0.9	≥80	100-277VAC	1900-6500K	2470±200lm	E26 Φ64*156	minus 40~60°C	NW 0.30kg	LM79 TM21 UL/cUL/RoHS UL1598C	75w MHL/HPS
							G24-Q Φ64*144				
							G24-D Φ64*151	minus 40~140°F	GW 0.35kg		
24W	72 leds SMD5630	≥0.9	≥80	100-277VAC	1900-6500K	3120±200lm	E26 Φ64*171	minus 40~60°C	NW 0.35kg	LM79 TM21 UL/cUL/RoHS UL1598C	100w MHL/HPS
							E39 Φ64*196				
							G24-Q Φ64*159	minus 40~140°F	GW 0.40kg		
							G24-D Φ64*166				

Features

REPLACE

LG 5630
130lm/W

360° beam angle

Flame retardant material

IP64 waterproof design

Advantages

***Great cooling structure**
*6063 aviation Aluminium
Bear low/high temp. -40 to 60°C
OK for totally enclosed fixture

***Beehive radiation holes**
Lead air flowing & low heat
Water run out & waterproof

***Special patent design**
*Separated LED and driver
*Prevent heat mutual conduction
*Easily replacement & maintain

***High efficiency LED**
SMD5630 130lm/w

***Base protector**
Ensure no broken when shipment

LG

lamp body more shorter and thinner,
suitable for different bollard fixtures.

1

driver
air passage
Heat sink

Isolated driver, better for heat dissipation

2

No Fan for heat dissipation solution

JAE Japan JAE connector
Easy driver replacement

Top quality driver components:
★FIRST MOS(USA)
★MPS IC CHIP(USA)
★RUBYCON CAPACITOR(JAPAN)
★GALAXY DIODES (biggest in China)

4

Driver with heat sink silicone for waterproof, dust proof and anti-mosquitoes