

PRODUCT DATASHEET

LUMIstixx

LUMIstixx | Little helpers



AREAS OF APPLICATION

- Sideboards
- Flower arrangements
- Practical adhesive surface or drill holes
- Horizontal or vertical alignment on walls or objects

PRODUCT BENEFITS

- Very compact LED luminaire

PRODUCT FEATURES

- Modern luminaire



TECHNICAL DATA**Electrical data**

Nominal wattage	0.6 W
Nominal voltage	4.5 V

Photometrical data

Color temperature	6200 K
Luminous flux	25 lm
Luminous efficacy	41 lm/W

Dimensions & weight

Length	222.0 mm
Diameter	16.2 mm
Height	21.0 mm
Product weight	70.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	White

Temperatures & operating conditions

Ambient temperature range	0...+25 °C
----------------------------------	------------

Lifespan

Lifespan	10000 h
-----------------	---------

Additional product data

Mounting location	Wall
Equipped with lamp	Yes

Capabilities

Type of installation	Surface-mounted
Adjustable	Yes
With on/off switch	Yes

Certificates & standards

Type of protection	IP20
Standards	CE

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321612649	LUMIstixx	Blister 2	244 mm x 29 mm x 93 mm	0.66 dm ³	203.00 g
4008321612656	LUMIstixx	Shipping carton box 12	151 mm x 305 mm x 100 mm	4.61 dm ³	1338.00 g
4008321612663	LUMIstixx	Shipping carton box 72	563 mm x 174 mm x 303 mm	29.68 dm ³	8729.00 g
4052899193888	LUMIstixx	Blister 1	283 mm x 110 mm x 25 mm	0.78 dm ³	165.00 g
4052899193895	LUMIstixx	Shipping carton box 6	314 mm x 193 mm x 121 mm	7.33 dm ³	825.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.