

PRODUCT DATASHEET ENDURA STYLE Ellipse 13 W DG

ENDURA STYLE ELLIPSE | Decorative and very bright luminaires



AREAS OF APPLICATION

- Outdoor
- Gardens, balconies and other outdoor areas
- Building facades
- Pathway lighting
- Driveways

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation

PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP44
- Die-cast aluminum housing
- Available as wall and bollard luminaires



TECHNICAL DATA


Electrical data

Operating mode	Mains voltage
Nominal wattage	12.50 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 К
Color rendering index Ra	>80
Light color (designation)	Warm White
Luminous flux	890 lm
Luminous efficacy	71 lm/W

Dimensions & weight



Length	161.0 mm
Width	186.0 mm
Height	75.0 mm
Product weight	1000.00 g

Colors & materials

Body material	Aluminum
Housing color	Dark gray
Product color	Dark gray
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-2040 °C

Lifespan

Lifespan	30000 h

Additional product data

Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Terminal

Certificates & standards

Protection class	1
Type of protection	IP44

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075033337	ENDURA STYLE Ellipse 13 W DG	Shipping carton box 4	390 mm x 240 mm x 210 mm	19.66 dm³	5226.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.