

PRODUCT DATASHEET

SILARA SPARKLE 450 24 W 830 Click-DIM

SILARA Sparkle | LED ceiling luminaires with sparkling effect



AREAS OF APPLICATION

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

PRODUCT BENEFITS

- Very homogenous light
- Easy and quick installation

PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Circular light emission



TECHNICAL DATA


Electrical data

Nominal wattage	24.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	>80
Light color (designation)	Warm White
Luminous flux	2000 lm

Dimensions & weight



Diameter	450.0 mm
Height	91.0 mm
Product weight	1278.00 g

Colors & materials

Body material	Metal
Housing color	White
Product color	White

Additional product data

Mounting type	Surface
Mounting location	Ceiling

Capabilities

Dimmable	Yes
-----------------	-----

Type of connection	Terminal, 3-Pole (L, N, PE)
---------------------------	-----------------------------

Certificates & standards

Protection class	I
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075042230	SILARA SPARKLE 450 24 W 830 Click-DIM	Shipping carton box 6	837 mm x 565 mm x 575 mm	271.92 dm ³	10380.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.