

# PRODUCT DATASHEET

## LED WORKLIGHT TRIPOD 2X50 W 4000 K

WORKLIGHTS - TRIPOD | Versatile LED worklight with tripod stand



---

### AREAS OF APPLICATION

- Renovation
- Garages
- Basement
- Workshops

---

### PRODUCT BENEFITS

- Foldable for easy storage
- Energy savings of up to 80% compared to halogen lamp worklights
- Semi-frosted, tempered glass cover for uniform illumination

---

### PRODUCT FEATURES

- Available with 1 or 2 luminaire heads
- Rotation angle luminaire head: 360°, swiveling: 180°
- Type of protection: IP65
- Height adjustment of tripod up to 1.8 m total height
- Quick-release fastener for adjustment of luminaire head angle
- Type E/F plug



**TECHNICAL DATA**


Electrical data

Nominal wattage	100.00 W
Operating mode	Electronic control gear (ECG)
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	9000 lm
Luminous efficacy	90 lm/W

Dimensions & weight



Length	780.0 mm
Width	680.0 mm
Height	1800 mm
Product weight	4800.00 g

Colors & materials

Body material	Aluminum/Steel
Housing color	Dark gray
Product color	Dark gray
Housing color	Dark gray
Cover material	Glass

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

## Additional product data

<b>Mounting type</b>	Standing
<b>Mounting location</b>	Floor
<b>Product remark</b>	Available from July 2019

## Capabilities

<b>Dimmable</b>	No
<b>Adjustable</b>	Yes
<b>Type of connection</b>	Protective contact Plug (type E/F)
<b>LED module replaceable</b>	Not replaceable

## Certificates &amp; standards

<b>Protection class</b>	I
<b>Type of protection</b>	IP65
<b>Standards</b>	CE/EAC/REACH/ROHS

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075213999	Folding carton box 1	182 mm x 229 mm x 644 mm	5059.00 g	26.84 dm <sup>3</sup>
4058075214002	Shipping carton box 4	475 mm x 380 mm x 665 mm	21266.00 g	120.03 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.