

PRODUCT DATASHEET

SMART+ ZB CANDLE 40 6 W E14

SMART+ Candle Tunable White | Classic candle shape with ZigBee technology



AREAS OF APPLICATION

- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Easy to install and use
- Up to 80 % less energy consumption compared to halogen lamps
- Contains no mercury

PRODUCT FEATURES

- LED Classic B lamp with wireless smart lighting function
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Network protocol: ZigBee
- Lifetime: up to 15,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality connection to a compatible smart home System (gateway and app) required



TECHNICAL DATA

Electrical data

| | |
|----------------------------------------|-------------|
| Operating frequency | 50...60 Hz |
| Rated wattage | 5.00 W |
| Power factor λ | > 0.50 |
| Nominal wattage | 5.00 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 40 W |


Photometrical data

| | |
|-----------------------------------------|---------------------------|
| Light color (designation) | Tunable White |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Standard deviation of color matching | ≤ 6 sdc _m |
| Adjustable color temperature | 2700...6500 K |
| Rated luminous flux | 470 lm |
| Nominal luminous flux | 470 lm |
| Color rendering index Ra | >80 |

Light technical data

| | |
|---------------------|------------------------------|
| Starting time | < 0.5 s |
| Light control | Adjustable color temperature |
| Warm-up time (60 %) | 0.50 s |

Dimensions & weight



| | |
|----------------|----------|
| Product weight | 32.00 g |
| Outer bulb | B40 |
| Length | 114.0 mm |
| Diameter | 38.0 mm |
| Overall length | 114.0 mm |

| | |
|-------------------------|---------|
| Maximum diameter | 38.0 mm |
|-------------------------|---------|

Lifespan

| | |
|-----------------------------------|---------|
| Number of switching cycles | 100000 |
| Rated lamp life time | 20000 h |
| Nominal lamp life time | 20000 h |

Additional product data

| | |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mercury-free | Yes |
| Show WEEE picto | Yes |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/Reset settings to default by switching the product on for five seconds and off for five seconds and repeating this five times. |
| Base (standard designation) | E14 |

Capabilities

| | |
|-----------------------------------------|-----------------------------------------------|
| Dimmable | Yes |
| Compatible smart home technology | Philips Hue / Google Assistant / Amazon Alexa |

Certificates & standards

| | |
|--------------------------------|-------------|
| Energy efficiency class | A+ |
| Energy consumption | 5 kWh/1000h |

EQUIPMENT / ACCESSORIES

- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075208414 | Folding carton box 1 | 61 mm x 96 mm x 154 mm | 103.00 g | 0.90 dm ³ |
| 4058075211605 | Shipping carton box 4 | 210 mm x 165 mm x 135 mm | 533.00 g | 4.68 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.