

# **PRODUCT DATASHEET** SMART+ Filament ZigBee Classic Edison 55 6W

SMART+ Filament Edison Dimmable | Edison bulb shape with filament-style with ZigBee technology



## **AREAS OF APPLICATION**

- General illumination

- Outdoor applications only in suitable luminaires

#### **PRODUCT BENEFITS**

- Easy to install and use
- Energy savings of up to 90 % (compared to halogen lamps)
- Contains no mercury

#### **PRODUCT FEATURES**

- LED Classic Edison lamp with wireless smart lighting function
- Dimmable
- Network protocol: ZigBee
- Lifetime: up to 15,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality connection to a compatible smart home System (gateway and app) required



# **TECHNICAL DATA**

## Electrical data

| Operating frequency                    | 5060 Hz  |
|--|----------|
| Rated wattage                          | 6.00 W   |
| Power factor λ                         | > 0.50   |
| Nominal wattage                        | 6.00 W   |
| Nominal voltage                        | 220240 V |
| Claimed equiv. conventional lamp power | 55 W     |


## Photometrical data


| Light color (designation)               | Warm Comfort Light |
|---|--------------------|
| Lumen main.fact.at end of nom.life time | 0.70               |
| Standard deviation of color matching    | ≤6 sdcm            |
| Rated luminous flux                     | 680 lm             |
| Nominal luminous flux                   | 680 lm             |
| Rated color temperature                 | 2400 К             |
| Color rendering index Ra                | ≥80                |

## Light technical data

| Starting time       | < 0.5 s  |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |

## Dimensions & weight





| Product weight   | 51.00 g  |
|------------------|----------|
| Outer bulb       | ST64     |
| Length           | 162.0 mm |
| Diameter         | 64.0 mm  |
| Overall length   | 162.0 mm |
| Maximum diameter | 64.0 mm  |

Lifespan

| Number of switching cycles | 100000  |
|----------------------------|---------|
| Rated lamp life time       | 15000 h |
| Nominal lamp life time     | 15000 h |

#### Additional product data

| Mercury-free                | Yes  |
|-----------------------------|--|
| Show WEEE picto             | Yes  |
| Product remark              | All technical parameters apply to the entire lamp/Due to the complex<br>production process for light-emitting diodes, the typical values shown for<br>the technical LED parameters are purely statistical values that do not<br>necessarily match the actual technical parameters of each individual<br>product, which can vary from the typical value |
| Base (standard designation) | E27  |

#### Capabilities

| Dimmable | Yes |
|----------|-----|
|          |     |

#### Certificates & standards

| Energy efficiency class | A++         |
|-------------------------|-------------|
| Energy consumption      | 6 kWh/1000h |

#### **EQUIPMENT / ACCESSORIES**

- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075528192 | Folding carton box<br>1      | 111 mm x 114 mm x 183 mm             | 130.00 g     | 2.32 dm <sup>3</sup> |
| 4058075528208 | Shipping carton box<br>4     | 243 mm x 238 mm x 199 mm             | 712.00 g     | 11.51 dm³            |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.